

Connects Fractional Tube to Female NPT Thread

Finetech Part No	T Tube OD (in.)	P-NPT Male Pipe Size (in.)	A	Ax	B	C	D	E Minimum Opening	F Wrench Pad	G Hex Flat	H	Hx	Hy
FTMBT10	01/08/10	01/08/10	1.86	0.93	0.38	0.6	0.5	0.09	07/16/10	07/16/10	1.34	0.67	0.7
FTMBT11	01/08/10	01/04/10	1.94	0.97	0.56	0.6	0.5	0.09	01/02/10	07/16/10	1.42	0.71	0.92
FTMBT12	03/16/10	01/08/10	1.92	0.96	0.38	0.63	0.54	0.12	07/16/10	01/02/10	1.4	0.7	0.7
FTMBT13	01/04/10	01/08/10	2.12	1.06	0.38	0.7	0.6	0.19	01/02/10	09/16/10	1.54	0.77	0.74
FTMBT14	01/04/10	01/04/10	2.12	1.06	0.56	0.7	0.6	0.19	01/02/10	09/16/10	1.54	0.77	0.92
FTMBT15	05/16/10	01/08/10	2.34	1.17	0.38	0.73	0.64	0.19	05/08/10	05/08/10	1.76	0.88	0.82
FTMBT16	03/08/10	01/04/10	2.4	1.2	0.56	0.76	0.66	0.28	05/08/10	11/16/10	1.82	0.91	1
FTMBT17	03/08/10	03/08/10	2.62	1.31	0.56	0.76	0.66	0.28	13/16	11/16/10	2.04	1.02	1.11
FTMBT18	01/02/10	03/08/10	2.84	1.42	0.56	0.86	0.9	0.38	13/16	07/08/10	2.04	1.02	1.11
FTMBT19	01/02/10	01/02/10	2.84	1.42	0.75	0.86	0.9	0.41	13/16	07/08/10	2.04	1.02	1.3
FTMBT20	05/08/10	01/02/10	3.06	1.53	0.75	0.86	0.96	0.47	1	1	2.26	1.13	1.41
FTMBT21	03/04/10	03/04/10	3.14	1.57	0.75	0.86	0.96	0.62	1 1/9	1 1/8	2.34	1.17	1.45

Connects Metric Tube to Female NPT Thread

Finetech Part No	T Tube OD (mm)	P-NPT Male Pipe Size (in.)	A	Ax	B	C	D	E Minimum Opening	F Wrench Pad (in.)	G Hex Flat	H	Hx	Hy
FTMBT10	6	01/08/10	53.9	27	9.7	17.7	15.3	4.8	01/02/10	14	39.1	19.6	18.8
FTMBT11	6	01/04/10	53.9	27	14.2	17.7	15.3	4.8	01/02/10	14	39.1	19.6	23.4
FTMBT12	8	01/08/10	59.7	29.9	9.7	18.6	16.2	4.8	05/08/10	16	44.7	22.4	20.8
FTMBT13	8	01/04/10	59.7	29.9	14.2	18.6	16.2	6.4	05/08/10	16	44.7	22.4	25.4
FTMBT14	10	01/04/10	67	33.5	14.2	19.5	17.2	7.1	13/16	19	51.8	25.9	28.2
FTMBT15	12	03/08/10	72	36	14.2	22	22.8	9.5	13/16	22	51.8	25.9	28.2
FTMBT16	12	01/04/10	72	36	14.2	22	22.8	7.1	13/16	22	51.8	25.9	28.2
FTMBT17	12	01/02/10	72	36	19	22	22.8	9.5	13/16	22	51.8	25.9	33
FTMBT18	16	01/02/10	77.6	38.8	19	22	24.4	11.9	1	25	57.4	28.7	35.8